



GVW (lbs.) 19,500
AXLE CAPACITY (lbs.) Front 7,280 / Rear 13,660
SPRING CAPACITY (lbs.) Front 8,000 / Rear 19,000
ENGINE (Hino) J08E-VC Diesel, 6-cylinder
 In-line, turbo intercooled
MAX. OUTPUT (HP) 220 @ 2,500 rpm
MAX. TORQUE (lb.-ft.) 520 @ 1,500 rpm
TRANSMISSION 6-speed Allison 1000 RDS
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 19.5 inch x 6.75 inch, 8 stud disc
TIRE SIZE 225/70R19.5

WHEELBASE CODES*

	G	J	L	M
WB	152.0	175.0	187.0	205.0
CA	84.6	107.6	119.6	137.6

2012 Model 198



GVW (lbs.) 25,500
AXLE CAPACITY (lbs.) Front 8,000 / Rear 17,500
SPRING CAPACITY (lbs.) Front 8,000 / Rear 19,000
ENGINE (Hino) J08E-VC Diesel, 6-cylinder
 In-line, turbo intercooled
MAX. OUTPUT (HP) 220 @ 2,500 rpm
MAX. TORQUE (lb.-ft.) 520 @ 1,500 rpm
TRANSMISSION
 Standard 6-speed direct drive Eaton FS5406A
 Automatic (Opt.) 6-speed Allison 1000 RDS
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 19.5 inch x 6.75 inch, 8 stud disc
TIRE SIZE 245/70R19.5

WHEELBASE CODES*

	L	M	P	R	T	V
WB	187.0	205.0	217.0	235.0	253.0	271.0
CA	119.6	137.6	149.6	167.6	185.6	203.6

MKLINEUP12E

Truck shown with optional equipment.

2012 Model 258LP



2012

www.hinocanada.com





Truck shown with optional equipment.

GVW (lbs.)
AXLE CAPACITY (lbs.)
SPRING CAPACITY (lbs.)
ENGINE (Hino)

26,000
 Front 10,000 / Rear 19,000
 Front 12,000 / Rear 19,000
 J08E-VC Diesel, 6-cylinder
 In-line, turbo intercooled
 220 @ 2,500 rpm
 520 @ 1,500 rpm

MAX. OUTPUT (HP)
MAX. TORQUE (lb.-ft.)
TRANSMISSION

6-speed direct drive Eaton FS5406A
 6-speed Allison 2200 RDS
 Hydraulic disc front and rear
 22.5 inch x 8.25 inch, 10 stud disc
 11R22.5

Standard
 Automatic (Opt.)

SERVICE BRAKES
WHEELS
TIRE SIZE

WHEELBASE CODES*

	L	M	P	R	T	V
WB	187.6	205.0	217.0	235.0	253.0	271.0
CA	119.6	137.6	149.6	167.6	185.6	203.6

2012 Model 268



Truck shown with optional equipment.

GVW (lbs.)
AXLE CAPACITY (lbs.)
SPRING CAPACITY (lbs.)
ENGINE (Hino)

33,000
 Front 12,000 / Rear 21,000
 Front 12,000 / Rear 21,000
 J08E-VB Diesel, 6-cylinder
 In-line, turbo intercooled
 260 @ 2,500 rpm
 660 @ 1,500 rpm

MAX. OUTPUT (HP)
MAX. TORQUE (lb.-ft.)
TRANSMISSION

6-speed direct drive Eaton FS6406A
 6-speed Allison 2500 RDS
 Hydraulic disc front and rear
 22.5 inch x 8.25 inch, 10 stud disc
 11R22.5

Standard
 Automatic (Opt.)

SERVICE BRAKES
WHEELS
TIRE SIZE

WHEELBASE CODES*

	L	M	P	R	T	V
WB	187.6	205.0	217.0	235.0	253.0	271.0
CA	119.6	137.6	149.6	167.6	185.6	203.6

2012 Model 338



Truck shown with optional equipment.

GVW (lbs.)
AXLE CAPACITY (lbs.)
SPRING CAPACITY (lbs.)
ENGINE (Hino)

35,000
 Front 14,000 / Rear 23,000
 Front 14,000 / Rear 23,000
 J08E-VB Diesel, 6-cylinder
 In-line, turbo intercooled
 260 @ 2,500 rpm
 660 @ 1,500 rpm

MAX. OUTPUT (HP)
MAX. TORQUE (lb.-ft.)
TRANSMISSION

6-speed direct drive Eaton FS6406A
 6-speed Allison 2500 RDS
 Full air
 22.5 inch x 8.25 inch, 10 stud disc
 11R22.5

Standard
 Automatic (Opt.)

SERVICE BRAKES
WHEELS
TIRE SIZE

WHEELBASE CODES*

	L	M	P	R	T	V
WB	187.6	205.0	217.0	235.0	253.0	271.0
CA	119.6	137.6	149.6	167.6	185.6	203.6

2012 Model 358

*See dealer for wheelbase availability

WB: Distance between the centerline of the front and rear axles
 CA: Distance from the back of the cab to the centerline of the rear axle